

Sustainable Geotechnical Engineering: Bridging Research and Industry

Khoa D.V. Huynh

khoa.d.v.huynh@ngi.no

EPFL Laboratory of Soil Mechanics

07/11/2024

Acknowledgment of Contributions from NGI Colleagues

My Geo-Journey & TEA




Outline






NGI in brief





Market areas

- 1. GeoData & Technology
- 2. Geotechnics & Environment
- 3. Natural Hazards
- 4. Offshore Energy




Offshore Energy

- 1. Computational Geomechanics
- 2. Energy Geomechanics and Geophysics
- 3. Geohazards and Dynamics
- 4. Offshore Geotechnical Characterisation
- 5. Offshore Geotechnical Design



NGI Lab



"Sans laboratoires les savants sont des soldats sans armes."

— Louis Pasteur (1822-1895)




NGI lab, Blinderen 1955



NGI lab, Oslo 2020

One of the largest geotechnical laboratories in the world



"It doesn't matter how beautiful your theory is, it doesn't matter how smart you are. If it doesn't agree with experiment, it's wrong." — Richard P. Feynman (1918-1988)





NGI - Fully Immersed in Geosciences

70 years of experience integrating geosciences

selection








and monitoring







Computational Geomechanics (CGM)



Overlapping/Complementary Skills and Resources






Core Services/Activities


Interpretation of lab and model tests



Advanced numerical modelling



Development of constitutive models





Development of calculation tools





Offshore Energy: from Oil & Gas to Wind





TAILOR MADE

- Single structure (platform or buoy)
- Typically a large and robust structure
- Cyclic loads from waves dominates
- Designed to high HSE standard
- Large return of investment


New philosophy and optimised workflows for field characterisation, design, fabrication & installation

MASS PRODUCTION


- Array of structures (OWTs)
- Typically slender structures
- Different dynamic characteristics
- Unmanned, so allow lower reliability
- Limited return of investment




Offshore Wind Turbine Foundations




Offshore Foundation Design





Offshore Foundation Design




Response based on laboratory results (stress path dependent)!




Monotonic Loading

- NGI-ADP material model:
 - Input parameters for (undrained) shear strength for three different stress paths/ states (Active, Direct Simple Shear, Passive)
 - A yield criterion based on a translated approximated Tresca criterion.
 - Elliptical interpolation functions for plastic failure strains and for shear strengths in arbitrary stress paths.
 - Isotropic elasticity, given by the unloading/reloading shear modulus, Gur.
- Additional features: Strain softening, Strain rate, Non-local strain, SHANSEP NGI-ADP
- Available in different programs: Plaxis, Bifurc, Abaqus, Anura MPM, etc.








Cyclic Loading: How Does Soil Behave?

Cyclic loading generates pore pressure



Pore pressure & shear strain increase with

time


time

 τ_0

u

no. of cycles

Cyclic and average shear stresses





Cyclic and average and permanent shear strains




Cyclic Loading: NGI Cyclic Contour Diagrams

- Monotonic tests (DSS, Triaxial Comp./Ext.)
- Cyclic tests
- Constant rate of strain (oedometer)









Cyclic Loading: NGI Cyclic Contour Diagrams

Cake contours



Basket ball contours



Prepared by Ana Page

Linda Hårvik



Cyclic Loading: NGI Procedure for Cyclic Soil Degradation

- Cyclic contour diagrams
- Cyclic loading parcels

- NGI procedure
- Cyclic degradation of soil stiffness and shear strength

Soil model: UDCAM, PDCAM


(available in FE programs: Bifurc, Plaxis, Abaqus, etc.)

UDCAM: UnDrained Cyclic Accumulation Model


PDCAM: Partially Drained Cyclic Accumulation Model



Cyclic Loading: Accumulation Procedure of UDCAM-S




1G model test of Troll Platform





Large Deformation Analyses

- Stability, run-out
- Installation effects
- Set-up effects
- Soil-structure interactions
- Capacity, stiffness
- In-built material models
- UDSM: NGI's in-house models, HP, Sanisand, etc.






Large Deformation Analyses


Examples of Penetration analyses


Penetrometer tests (CPT, T-bar, Ball)






Validation against centrifuge tests





Spudcan penetration on existing footprint






Large Deformation Analyses


Examples of Drivability assessment

Centrifuge Suction caissons






Monopiles w/wo driving shoes




Fluke anchor capacity for anchoring floating structures



Calculation Tools


• In-house programs

Programs	Brief description
ACCUMUL	Shear strain and pore pressure accumulation during cyclic loading
GroundModel	Integrated ground model
SPLAT	Calculate spudcan penetration using ISO/SNAME methods
SWIFT	Foundation capacity assessment for jack-up vessels







SPudcan Leg Analysis Tool (SPLAT)



Different stages of penetration







l				
3. OTHER ANALYSIS P.				
Load spread factor	3		THE UNIVERSITY OF	
Squeezing factor	3		NGI WESTERN AUSTRALIA	
Backflow mode	calculate		ALISTRALIA	
Incremental size (fraction of R)	0.01		AOSTALIA	
Final tip penetration (m)	20			
Leg buoyancy (kN/m)	0			
Preload per leg (MN)	210.8			
Calcualtion method	Second Run			
metnod				
CALCULATION METHOD	GUIDELIN	VES	NOTE	
CALCOLATION METHOD	GCIDEEII	120	SINGLE CLAY LAYER	
Skempton (1951)	Iso	Average s., in 0.51	D below footing base is used, dc= 1 + 0.2*d/B \leq 1.5	
Brinch Hansen (1970)	SNAME		Average 5, in 0.25D below the footing base is used. de = 1 + 0.4arctan(dD)	
Martin Houlsby (2003)	SNAME Comm /IS	SO/INSAFE s., taken as the str	s, taken as the strength at footing base, soil heiterogening, conical shape, roughness, embedment considered	
Hossain and Randolph (2009a, b)		s., taken as the ste	5. taken as the stength at footing base, relevant mechanisms at various stages of penetration explicitly considered	
Py since to the recigion of revenue succession of signs of prevenues regions regions of prevenues regions regions of prevenues regions reg				
Brinch Hansen (1970)	SNAME Comm.	φ reduced by 5° fr	φ reduced by 5° from lab traxial results for input	
Vesic (1975)	SNAME	øreduced by 5° fro	preduced by 5° from lab traxial results for input	
Martin ABC	ISO	N _n N _n factors bas	N _o , N _o factors based on results from Martin's ABC program, consideration should be given to choose the appropriate φ	
INSAFE (2011)	INSAFE	Use Cassidy and I	Use Cassidy and Houlsby (2002) N_x factors, peak ϕ as input, a reduction factor $F_{mob} = 0.25 \cdot 0.5$ and a roughness = 0.5 recommended	
MULTI LAYERS (no. of layers ≥ 2)				
Pre Run		Apply general shear to all layers, no treatment of conical shape at layer interface		
First Run		Apply general she	Apply general shear to all layers, with treatment of conical shape at layer interface	
Second Run	SNAME/ISO	Apply general shear/punch through squeezing mechanims judged on the Pre Run capacity, with treatment of conical shape at layer interface. For stiff clay overlying soft clay, the Brown and Meyerhof (1969) method is used; for sand overlying clay, the load spread method is used; for clay overlying stiff sold, the squeezing equation by Meyerhof and Chaplin (1953) is used.		
ADDITIONAL METHOD ONLY FOR TWO LAYERS				
Hossain and Randolph (2009c)	Recommended in II	NSAFE For stiff clay over	soft clay, punch-through type site	
Hanna and Meyerhof (1980)	SNAME/ISO	Punching shear me	Punching shear method for sand over clay profile, K_s value read from graph based on ϕ and $Q_{\rm clay}/Q_{\rm 1800}$	
Hu et al. (2013)	Allowed in ISO, IN	Allowed in ISO, INSAFE Stress dependent model for sand over clay profile, constant volume friction angle φ _{cc} and relative density I _d are required for sand		



Data-Driven Geotechnics - Ground Model to Design













Integrated geomodel (G⁴)

- Data integration and cross-correlation, supported by physical models, statistics and machine learning
- Provides fundamental geotechnical design basis for entire 3D seabed cube
- Includes both parameters and associated uncertainty

Foundation design

- Input drawn from ground model
- Rapid sizing across wind farm
- Screening of entire lease area for optimal dimensions ("zonation heat maps")
- Streamline approach allows iterations and updates through project phases
- Works for standard foundations like monopiles, GBSs, suction bucket jackets etc (Different load input needed)

Data collection

- High quality geophysics
- In-situ testing (including S wave)
- Laboratory testing
- Imported into unified database



Integrated Ground Model - Overview

• Quantitative ground model combining geology, geophysical and geotechnical data

Geophysics Geostatistics


Geology


Geotechnics

Integrated ground model

- Geophysical: 2D seismic profile
- Geotechnical: CPT tests (q_c)

e learning techniques to create a 3D volume of geotechnical data for design









Vanneste et al. 2022, Sauvin et al. 2019

Data-Driven Geotechnics - Ground Model






Ground Model to Foundation Design




Teliable technical models






Geotechnical design



Structural design






Foundation stiffness
Global (REDWIN)
or local (PISA)
Springs for load
and fatigue analysis



Ground Model to Petroleum Geomechanical Modeling



- 2D and 3D geomechanical modeling in FE Tools (i.e. Plaxis, Abaqus, Comsol...)
- Coupling of field scale model towards 4D seismic interpretation and detailed models for wellbore and fault stability.

Routines for data import


- Detailed geometry and property distribution from seismic horizons and geological model (i.e. RMS or Petrel)
- Detailed pore pressures distribution (from reservoir simulator i.e. ECLIPSE simulations).

Petrophysical properties dependent mechanical properties



- Reservoir: Petrophysical data (e.g. porosity, NTG)
- Overburden/cap rock: Geophysical data (e.g. Vp)
- · Seabed: CPT data
- Stress: 3D density cube and K0 ratio


Fully Integrated Analyses Including Seabed Soil










Fully Integrated Analyses Including Seabed Soil



Macro-Model for Spudcan Foundations









Virtual Lab for Granular Materials

Database of sand grains

From X-ray Computed Tomography (XRCT) to «digital grains»











Torgersrud et al. 2024

Virtual Reality R & D






Environments Beyond Earth



Earth, Moon and Mars: Key Differences & Characteristics

Feature	Earth	Moon	Mars
Distance from Earth	-	384,000 km	~79 million km
Visitors	Over 8 billion (human)	24 human visitors, 12 walkers	None (8 robotic missions)
Atmosphere	Nitrogen, Oxygen	None	Carbon dioxide
Radius	6,371 km	1,740 km	3,389.5 km
Temperature range	-88°C to +58°C	-248°C to +120°C	-140°C to +30°C
Gravity	9.8 m/s ²	1/6 of Earth	1/3 of Earth
Atmospheric pressure	101.3 kPa	0.3 nPa	~0.6 kPa
Humidity	Varies	Very low (0.01-0.04%)	Very low (Arid)
Special features	Life, water, biosphere	Bombardment by solar wind, meteorites	Largest volcano & deepest canyon







Current Projects at NGI

Research projects:

- Lunar Regolith laboratory testing (Including Apollo 14 samples)
- Icy regolith characterization (frozen lunar regolith ice content)
- Martian simulants strength characterization
- Shear wave velocity and particle shape effects (collaboration with France)
- LUNOR Norwegian Lunar Regolith Simulant
- Calibration Chamber


Commercial projects:

- Lunar soil simulants testing (2023-2024, ESA, URS)
- Martian Simulants characterization (2023-2026, ESA)




Lunar Simulants vs. Lunar Regolith

- Lunar simulants can't currently account for all aspects of the lunar regolith
- We processed and analysed X-ray nano CT images of regolith grains returned from the Apollo 11 and 14 missions and found some interesting shapes...




X-Ray Nano-CT scan of LHS-1






LS-DEM: Particle Morphology

NGI





LS-DEM: A Digital Twin of Lunar Soil

Simulations with varying gravity




Near vertical walls on the Moon due to high cohesion, frictional shear strength. NASA, from Carrier et al., Lunar Sourcebook (1991)






Through numerical simulation, we see that lower gravity leads to higher angle of repose.










Bridging Research and Industry







Floating structures for the next generation ocean industries




New ideas for concepts

New technology

Input





New products

New services

Spin-off projects

New design tools

Results and innovations

New design methods

Newly educated MSc's and Phd's

New knowledge

FME NorthWind

A strategic research and innovation action to reduce the cost of wind energy, facilitate its sustainable development, create jobs and grow exports

Partners: SINTEF (host), NTNU, NINA, NGI, UiO and 50 industry partners


Total budget 2021-2029: 350 MNOK financed by Research Council of Norway, industry and research partners





TAILWIND susTainable stAtion-keepIng systems for fLoating WIND

PROJECT OVERVIEW



















Remarks



Key Points

Interdisciplinary innovation Industry-Academia collaboration Data-driven decision making Sustainable practices Skill development and knowledge transfer Real-time application of advanced models



Key Actions

Establish joint research projects Develop specialized training programs Foster knowledge-sharing platforms Implement pilot projects for new technologies Incentivize sustainability-driven research Regularly review and update industry standards Create internship and exchange programs



Acknowledgment of Contributions from NGI Colleagues



Aligi Foglia



Jung Chan Choi



Ana Page



Nallathamby Sivasithamparam



Dylan Mikesell



Øyvind Torgersrud



Hans Petter Jostad



Santiago Quinteros

and many others





References

- Andersen, K.H., 1976. Publication: BEHAVIOUR OF CLAY SUBJECTED TO UNDRAINED CYCLIC LOADING. Norwegian Geotechnical Institute.
- Andersen, K.H., 2015. Cyclic soil parameters for offshore foundation design. Frontiers in offshore geotechnics III, 5, pp.5-82.
- Grimstad, G., Andresen, L. and Jostad, H.P., 2012. NGI-ADP: Anisotropic shear strength model for clay. International journal for numerical and analytical methods in geomechanics, 36(4), pp.483-497.
- Grimstad, G., Jostad, H.P. and Andresen, L., 2010, July. Undrained capacity analyses of sensitive clays using the nonlocal strain approach. In Proceedings of the 9th HSTAM international congress on mechanics, Vardoulakis mini-symposia, Limassol, Kypros (pp. 12-14).
- Jostad, H.P., Andersen, K.H., Khoa, H.D.V. and Colliat, J.L., 2015, May. Interpretation of centrifuge tests of suction anchors in reconstituted soft clay. In Proceedings of the 3rd International Symposium on Frontiers in Offshore Geotechnics, Oslo, Norway (pp. 269-276).
- Jostad, H.P. and Andresen, L., 2009, April. A FE procedure for calculation of displacements and capacity of foundations subjected to cyclic loading. In Proc., 1st Int. Symp. on Computational Geomechanics. Rhodes, Greece: Int. Center of Computational Engineering.
- Jostad, H., Grimstad, G., Andersen, K. and Sivasithamparam, N., 2015. A FE procedure for calculation of cyclic behaviour of offshore foundations under partly drained conditions. Frontiers in offshore geotechnics III, 1, pp.153-172.
- Jostad, H.P., Grimstad, G., Andersen, K.H., Saue, M., Shin, Y. and You, D., 2014. A fe procedure for foundation design of offshore structures—applied to study a potential owt monopile foundation in the korean western sea. Geotechnical Engineering Journal of the SEAGS & AGSSEA, 45(4), pp.63-72.
- Khoa, H.D.V. and Jostad, H.P., 2016. Application of coupled Eulerian-Lagrangian method to large deformation analyses of offshore foundations and suction anchors. International Journal of Offshore and Polar Engineering, 26(03), pp.304-314.
- Khoa, H.D.V. and Jostad, H.P., 2018. Application of a cyclic accumulation model UDCAM to FE analyses of offshore foundations. In Proceedings of the 4th Congrès International de Géotechnique-Ouvrages-Structures: CIGOS 2017, 26-27 October, Ho Chi Minh City, Vietnam 4 (pp. 656-667). Springer Singapore.



References (cont.)

- Khoa, H.D.V., Jostad, H.P. and Engin, H.K., 2019. Improvement of N T-bar Evaluation in Clays Using Large Deformation FE Method. In Proceedings of the 1st Vietnam Symposium on Advances in Offshore Engineering: Energy and Geotechnics (pp. 137-143). Springer Singapore.
- Klinkvort, R.T., Sturm, H., Page, A.M., Zhang, Y. and Jostad, H.P., 2020. A consistent, rigorous and super fast monopile design approach. In 4th International Symposium on Frontiers in Offshore Geotechnics, Austin, Texas, USA.
- Klinkvort, R.T. and Sivasithamparam, N., 2021. Design of monopiles supporting offshore wind turbines using finite element analysis. In Analysis of Pile Foundations Subject to Static and Dynamic Loading (pp. 83-106). CRC Press.
- Norén-Cosgriff, K., Jostad, H.P. and Madshus, C., 2015. Idealized load composition for determination of cyclic undrained degradation of soils. In Frontiers in Offshore Geotechnics III: Proceedings of the 3rd International Symposium on Frontiers in Offshore Geotechnics (ISFOG 2015) (Vol. 1, pp. 1097-1102). Taylor & Francis Books Ltd.
- Sauvin, G., Vanneste, M., Vardy, M.E., Klinkvort, R.T. and Carl Fredrik, F., 2019, April. Machine learning and quantitative ground models for improving offshore wind site characterization. In Offshore Technology Conference (p. D021S016R004). OTC.
- Sauvin, G., Vardy, M., Klinkvort, R.T., Vanneste, M., Forsberg, C.F. and Kort, A., 2022, November. State-of-the-art ground model development for offshore renewables–TNW case study. In EAGE GET 2022 (Vol. 2022, No. 1, pp. 1-5). European Association of Geoscientists & Engineers.
- Torgersrud, Ø., Ando, E., Jostad, H.P., Andrade, J., Viggiani, C., 2024. Microstructural investigation of granular soil upon drained cyclic loading. IS-Grenoble 2024: International Symposium on Geomechanics from Micro to Macro.
- Vanneste, M., Sauvin, G., Dujardin, J.R., Forsberg, C.F., Klinkvort, R.T., Forsberg, C.S. and Hansen, R.C., 2022. Data-driven ground models: the road to fully-integrated site characterization and design. In Proceedings of the 2nd Vietnam Symposium on Advances in Offshore Engineering: Sustainable Energy and Marine Planning (pp. 3-21). Springer Singapore.
- Zhang, Y.K., Khoa, H.D.V., Meyer, V. and Cassidy, M.J., 2015. Jack-up spudcan penetration analysis: Review of semi-analytical and numerical methods. In Frontiers in Offshore Geotechnics III: Proceedings of the 3rd International Symposium on Frontiers in Offshore Geotechnics (ISFOG 2015) (Vol. 1, pp. 1341-1346). Taylor & Francis Books Ltd.





On safe ground