Fundamentals of Traffic Operations and Control WEEK 1b Traffic Studies & Data Collection System Monitoring and ITS

Nikolas Geroliminis



Urban Transport
Systems Laboratory (LUTS)



Traffic Studies

- A traffic engineer's laboratory is the surrounding roadway system
- This system must be continually monitored, evaluated, and managed



Guiding Principles

- "If you cannot tell the system performance yesterday, you cannot hope to manage your system today."
 - -- Data Collection/Analysis
- "Data are too valuable to only use once."
 - -- Data Archive
 - -- Real Time and Historical



Traffic Studies

- Traffic demand/patterns will change over time, monitoring of system will enable necessary system changes to be identified
- The effects of system "improvements" must be justified, e.g.,
 - Signal timing changes
 - Lane additions or reconfigurations



Traffic Studies


- Data collection is the key foundation
 - What kind of data?
 - How much data?
 - How to collect it?
- The study characteristics must be considered in answering these questions, e.g.,
 - Short-term or long-term study
 - Statistical confidence level

4


Temporal Variation

- Monthly (Jan. Dec.)
- Daily (Sun. Mon.)
- Hourly (12:00 AM 11:59 PM)
- K values (e.g., K₁₀₀, K₃₀)
 - The ratio of the Xth highest traffic volume hour of the year to the AADT (Average Annual Daily Travel)
 - Historically, 30th has been used in rural planning, design and operations. (generally flatten out from this point)

Graphic Summary of Vehicle Movements



Traffic Counts Displayed in a Network



Vehicle Classification (VC)

- Volume with respect to vehicle type
 - Passenger cars
 - 2 axle trucks
 - 3 axle trucks
 - Public service vehicle (PSV)
 - Emergency vehicle
 - 2 wheel vehicles
- Applications
 - Geometric design (e.g., turning radii, max. grade, lane width)
 - Capacity Analysis (e.g., PCU conversions)
 - Automated counts
 - Pavement & Structure design

Vehicle Mile Travel (VMT)

- AADT x roadway length
- Applications:
 - Economic evaluation
 - Resource allocation (maintenance & improvement)
 - Planning

Measurement methods

- measurements at a (cross-sectional) point
- measurements along a short distance
- measurements along a length
- measurements along an arterial or small area (by e.g. moving observer method)
- other realtime large-scale monitoring methods

Measuring means

Measuring passage times, time headways, and flow

- manual counting, using a form and a stopwatch. Advantage: simple method; Disadvantage: labour costs and inaccuracies.
- Pneumatic tubes. Advantage: can accurately determine passage times and time headways; Disadvantage: relatively short time survival.
- Induction loops.
- Infrared detector.
- Instrumented vehicles (moving observer method).

Individual speeds, instantaneous, and local mean speed

- Radar speedometers at a cross-section.
- Induction loops or double pneumatic tubes.
- vehicle recognition.
- Probe vehicles.
- Remote-sensing techniques.

"Manual" counting













Pneumatic tube









Inductance Loops


Vehicle Loops



Bike Loops



Microscopic measurement at induction loops



A single-loop detector can directly measure (only):


- The time t_{α}^{0} at which the front of vehicle α passes the detector (voltage drop),
- The time t_{α}^1 at which the rear end of the vehicle passes the detector (voltage rise)



Inductance Loop Signatures (1)


Sport Car





Truck








Inductance Loop Signatures (2)


Pickup Truck





Trash Truck








Inductance Loop Signatures (3)


Tailgating vehicles





Vehicle with a boat





Density

- Aerial photographs
- Volume / Speed
- Surrogate measure from inductance loop detectors
 - Ratio of occupied time to total observation time, expressed as a percent, is termed 'lane occupancy', denoted by ϕ (phi)

$$\phi = \frac{\text{total occupied time}}{\text{total observation time}} *100$$

• To use lane occupancy for estimation of density, we must know vehicle length, then density can be estimated by


$$k = \frac{\phi}{100} = \frac{1}{L_e}$$
 Le is the effective vehicle length




Video Imaging




Autoscope software





Infra-red sensors



Laser guns






Travel times

- Comparable for different traffic modes
- easy to be used in traffic models
- can be perceived easily

measurement sensors


- Vehicle Plate Recognition
- GPS receivers
- Cellular antenas

Vehicle Plate Recognition



GPS receivers







Global Positioning System (GPS)

- GPS Time
- Latitude and Longitude
- Speed






Typical GPS Data


	Time	Latitude	Longitude/	Speed
	(UTC)	(°)	(°)	(mph)
	16:27:39	30.389885	-91.2424 <mark>2</mark> 6	40.0
	16:27:40	30.390090	-91.242276	40.6
	16:27:41	30.390159	-91.242225	40.7
	16:27:42	30.390298	-91.242122	41.0
	16:27:43	30.390507	-91.241966	41.8
١			•	

Cellular antennas




Bluetooth sensors










Estimate travel times between sensor points

Estimate O-D tables


Estimate average speeds

Electronic Toll Collection (AVI)




Origin-Destination (O-D) Studies


 Determining the percentage of all traffic traveling from each origin point of interest to each destination point of interest




Data Fusion

- the process of combining data from multiple, heterogeneous data sources such as cross-sectional data, floating-car data, police reports, etc.
- each of these categories of data describes different aspects of the traffic situation and might even contradict each other.
- the goal of data fusion is to maximize the utility of the available information.








Data: Autobahn A5 near Frankfurt/Main, Germany (sou

Collecting traffic data with drones

Complex interactions

- Multimodality
- Components adapt
- Competing operators
- Spreading phenomena



Limits to predictability

Limits to centralization

Limits to cooperation


Bird-eye view





different areas
















Complex traffic interactions



A new experiment











