## **Intelligent Agents**

Paper Exercise: Coalitions and Group Decisions

## **Solutions**

**Question 1:** Consider the following characteristic function for coalitions of four agents A, B, C and D:

А	1	AB	3	BD	4	ACD	6
В	1	AC	4	CD	4	BCD	6
С	2	AD	4	ABC	6	ABCD	8
D	1	ВС	3	ABD	7		

Figure 1: Game in characteristic function form.

Is this game superadditive? If not, what set of coalitions would be a counterexample?

**Answer:** No - counterexample: ABD and C has larger payoff than ABCD.

Is the grand coalition (ABCD) the best coalition structure? If not, what is the best coalition structure?

**Answer:** no, (ABD),© is the best structure.

**Question 2:** In the game of Figure 1, suppose that the payoff of the grand coalition is changed from 8 to 9. Is the game superadditive?

**Answer:** yes

Is the game convex? If not, what set of coalitions would be a counterexample?

**Answer:** no, counterexample:

ABC, ABD: p(ABC)+p(ABD)-p(AB) = 6+7-3 = 10 > 9 = p(ABCD).

What is the Shapley value of each agent in the coalition (ABD)?

Is this payoff distribution in the core?

**Answer:** (13/6, 13/6, 16/6), in the core.

For the following questions, consider the following voter preferences:

No. of voters	1 <sup>st</sup> choice	2 <sup>nd</sup> choice	3 <sup>rd</sup> choice
20	А	С	В
18	В	С	А
5	С	В	Α

## Question 3:

Is there a Condorcet winner? (yes - C)

Who wins in plurality voting? (A)

Who wins if alternative B is removed? (C wins)

Who wins if alternative C is removed? (B wins)

Who wins using plurality voting with elimination? (B)

Who wins using Borda counts? (C)

**Question 4:** How many voters would have to change to that C would win in plurality voting?

**Answer:** 10 would have to make C their most preferred choice, 6 from group 1 and 4 from group 2

**Question 5:** What manipulation will make candidate B win in plurality voting?

**Answer:** three members of third group vote for B instead of C

**Question 6:** Compute the Slater ranking for this example! How many voters would need to change to manipulate it?

**Answer:** (C,B,A),

2 voters would have to switch from ranking B over A to ranking A over B to to get (C,A,B).