

Distributed Algorithms

Consensus
4th exercise session

Matteo Monti <matteo.monti@epfl.ch>
Jovan Komatovic <jovan.komatovic@epfl.ch>

Exercise 1

(Consensus & Perfect failure detector)

Consider our fail-stop consensus algorithms (Consensus Algorithm I and Consensus Algorithm II). Explain why none of those algorithms would be correct if the failure detector turned out not to be perfect.

Exercise 2

(Consensus & Eventually perfect failure detector)

*Explain why **any** fail-noisy consensus algorithm (one that uses an eventually perfect failure detector $\Diamond P$) actually solves uniform consensus (and not only the non-uniform variant).*

Exercise 3

(Consensus & Correct majority)

*Explain why **any** fail-noisy consensus algorithm (one that uses an eventually perfect failure detector $\Diamond P$) requires a majority of the processes to be correct. More precisely, provide a “bad run” in the case where the majority of processes is faulty.*

Sequential Objects

A sequential object is a tuple $T = (Q, q_o, O, R, \Delta)$, where:

- Q is a set of *states*.
- $q_o \in Q$ is an initial state.
- O is a set of operations.
- R is a set of responses.
- $\Delta \subseteq (Q \times \Pi \times O) \times (Q \times R)$ is a relation that associates a state, a process, and an operation to a set of possible new states and responses.

Processes invoke operations on the object. As a result, they get responses back, and the state of the object is updated to a new value, following from Δ .

Guided Exercise 4

(Asset Transfer Object)

*Define a sequential object representing Asset Transfer, i.e., an object that allows processes to **exchange** units of currency.*

Bonus Exercise 5

(Total Order & Asset Transfer)

Use Total Order Broadcast to implement an Asset Transfer sequential object.