

CS-473: System programming for Systems on Chip

Practical work 4

Caches

Version:

1.0





Contents

1	Intr	oduction
	1.1	Prerequisites
	1.2	Objectives
	1.3	Requirements
2	Exe	rcises
	2.1	Structure Memory Layout and Caches
	2.2	Programming Tasks





1 Introduction

1.1 Prerequisites

On moodle you find the file cache.zip; it contains the complete source code template for this practical work. Download this file, and unzip it in the directory programms.

1.2 Objectives

In the scope of this practical work, you will learn about:

- 1. memory layouts of structures in C,
- 2. optimizing the memory layout for caches,
- 3. designing cache-friendly algorithms,
- 4. the interaction between I/O devices and caches.

1.3 Requirements

Make sure that:

- 1. the project files are downloaded and extracted,
- 2. your Gecko board has the final version of the firmware,
- 3. the toolchain is functional (it should be or1k-elf-gcc).

All the file paths mentioned in this document are relative to the downloaded archive.

Version: 1.0 Last change: 01/11/2024 page 1 of 8



2 Exercises

2.1 Structure Memory Layout and Caches



Please read "The Lost Art of Structure Packing" by Eric S. Raymond to answer the questions in this section. It is available at: http://www.catb.org/esr/structure-packing/.

Project cache_sweep under ./cache/sweep/ executes a C program summarized in Figure 2.1. The program contains a struct item_t consisting of an ID and data, an array of item_ts, and function items_find that finds an item_t with a given ID. The full source code of the program is available under ./cache/sweep/src/datapoint/datapoint.c. The executable contains multiple versions of this program for different configurations described by the following parameters:

- 1. PARAM_PACKED: item_t has the ___packed modifier or not.
- 2. PARAM_DATALEN: length of field data of struct item_t.
- 3. PARAM_COUNT: length of the array.

We aim to analyze how these parameters affect (1) the code generated by the compiler and (2) the number of data cache misses. Both plots in Figure 2.2 sweep PARAM_DATALEN. Figure 2.2a plots sizeof (item_t). Figure 2.2b plots the number of data cache misses for function items_find. For all the data points in Figure 2.2b, function items_find accesses all the array elements.

Questions:

- 1. What does the __packed modifier do? Note that __packed is defined in Figure 2.1. Online resources and the compiler manual might help you with this part of the practical work.
- 2. Explain the memory layout of item_t with and without __packed and for PARAM_DATALEN $\in \{1,2,3,4\}$. Specify (1) the ordering of the fields, (2) the size of each struct field, and (3) padding bytes (the processor has a 32-bit alignment). You do not need to make a table; however, be clear and concise!
- 3. Repeat the previous question for the memory layout of the array. Consider the first two array elements.
- 4. How does ___packed affect the number of cache misses? Why?
- 5. Consider the data series in Figure 2.2 that do not use __packed (i.e., the orange lines). What is the cache line size for the data cache? Explain your approach.
- 6. How does ___packed affect the generated assembly code size? Why? What does the compiler do differently? Generated assembly file for each data point is available under ./cache/sweep/build-release/src/datapoint/datapoint_COUNT_LENGTH_PACKED.s.

2.2 Programming Tasks




Please read Section 4 of "Cache-Conscious Data Structures" from Microsoft Research to answer the questions in this section. It is available at: https://www.microsoft.com/en-us/research/wp-content/uploads/2016/12/ccds.pdf.


page 2 of 8 Last change: 01/11/2024 Version: 1.0



```
/** @note defined in 'defs.h'. */
  #define __packed __attribute__((packed))
  /** @brief Item struct. Relates an 'id' to a piece of 'data'. */
  typedef struct __packed /* or nothing, depending on the configuration */ { uint32_t id;
      char data[PARAM_DATALEN];
  } item_t;
  /** @brief An array of items. */
  static item_t items[PARAM_COUNT];
   st @brief Searches for an item matching the 'id'.
14
     @param id
     @return item_t* Pointer to the found item.
18
  item_t* items_find(uint32_t id) {
      for (size_t = 0; i < PARAM_COUNT; ++i) {
          if (items[i].id = id)
               return &items[i];
      return NULL;
24
```

Figure 2.1: A simplified version of the measured program. Each data point consists of PARAM_DATALEN , PARAM_COUNT, and PARAM_PACKED. The program is compiled and executed for each data point. PARAM_PACKED determines if the struct has __packed modifier. For each data point, we record sizeof (item_t) and the number of data cache misses.





- (a) Structure size for varying data length.
- (b) Number of data cache misses for varying data length.

Figure 2.2: Both figures vary the data length (PARAM_DATALEN). Figure (b) is drawn for PARAM_COUNT=256. The number of memory accesses is same as PARAM_COUNT.

Version: 1.0 Last change: 01/11/2024 page 3 of 8



In this part of the assignment, you will modify the source of project cache_tasks under ./cache/tasks/. Take a look at the directory structure and understand it. The project can be built, as usual, by the following commands:

```
cd ./cache/tasks # enter the project directory

# before executing make, make sure that the toolchain is in the PATH

export PATH=/opt/or1k_toolchain/bin/:$PATH

# build the mem file ready to be uploaded make mem1300

# clean the built files make clean

# build and keep the intermediate assembler files for inspection make mem1300 CFLAGS=—save—temps

# build and also print the linker map make mem1300 CFLAGS=—save—temps LDFLAGS=—WI,——print—map
```

As a first step, please check your setup:

- 1. Compile the project as described.
- 2. Upload the .cmem file and execute the program. Note that uploading might take up to 10 seconds.

The expected program output is the following (cache miss numbers might be slightly different):

```
task1 main
    sizeof(node_t) = 64:
    struct layout for node_t:
                                                                                        −> offset
  member
    node . i d
                                                                                                              -> 0 \times 000
  node.data
                                                                                                            -> 0×004
                                                                                                      -> 0x038
   node.next
                                                                                                            −> 0x03c
    node.prev
  \#0 \  \  \, \rightarrow \  \, \#11 \  \  \, \rightarrow \  \, \#12 \  \  \, \rightarrow \  \, \#2 \  \  \, \rightarrow \  \, \#4 \  \  \, \rightarrow \  \, \#1 \  \  \, \rightarrow \  \, \#15 \  \  \, \rightarrow \  \, \#14 \  \  \, \rightarrow \  \, \#14 \  \  \, \rightarrow \  \, \#15 \  \  \, \rightarrow \  \, \#14 \  \  \, \rightarrow \  \, \ \, \rightarrow \  \, \#14 \  \  \, \rightarrow \  \, \ \, \rightarrow \  \, \, \ \, \rightarrow \  \, \, \rightarrow \  \, \, \rightarrow \  \, \rightarrow \  \, \, \rightarrow \  \,
                               \#13 \ -\!\!\!> \ \#10 \ -\!\!\!> \ \#5 \ -\!\!\!> \ \mathsf{Done} \,.
  Task 1: dcache misses:
   task2_main
Item ID = 15, data = random data: 11
   Task 2: dcache misses:
 task3_main
  Task 3: dcache misses:
                                                                                                                                                                                                                     65893
 out_vector verification successful!
   task4_main
  original address: 0x50000800
   new address: 0x08000800
```

page 4 of 8 Last change: 01/11/2024 Version: 1.0

CS-473 SPSOC Caches



Task 1: Optimize node_t

Consider the following source files:

- ./cache/tasks/src/task1.c
- ./cache/tasks/src/node.c
- ./cache/tasks/include/node.h

struct node_t is defined in node.h and function node_count is defined in node.c:

```
#define NODE_DATALEN 52
  typedef struct node_t node_t;
   * @brief Defines a node.
   * @note **Do not remove** any fields from this structure.
  struct node_t {
   /** @brief Node ID. */
10
      unsigned id;
      /** @brief Node data. */
      char data[NODE_DATALEN];
14
      /** @brief The next node. */
16
      node_t* next;
      /** @brief The previous node. */
      node_t* prev;
20
  };
  uint32_t node_count(node_t* node) {
      // YOU ARE NOT SUPPOSED TO MODIFY THIS.
24
      uint32_t result = 0;
      while (node) {
28
           printf("#%u -> ", node->id);
           result++;
30
           node = node->next;
32
      printf("Done.\n");
34
36
      return result;
```

Questions:

- 7. What accesses in function node_count cause cache misses? Why?
- 8. Propose a strategy to decrease the number data cache misses caused by function <code>node_count</code>. Test your approach on the Gecko board. What is the new number of cache misses? Do not modify the functions or remove fields from struct <code>node_t</code>.



Note that node_count is unlikely to access node_ts that are adjacent in memory.

Version: 1.0 Last change: 01/11/2024 page 5 of 8

CS-473 SPSOC Caches



Task 2: Optimize item_t

Consider the following source files:

- ./cache/tasks/src/task2.c
- ./cache/tasks/src/item.c
- ./cache/tasks/include/item.h

struct item_t is defined in item.h; functions items_find and item_init are defined in item.c:

```
#define ITEM_DATALEN 32
  typedef struct item_t item_t;
   * Obrief An item connects an 'id' to 'data'.
  struct item_t {
       /** @brief Item ID. */
       unsigned id;
       /** @brief Item data. */
       char data[ITEM_DATALEN];
14
  };
16
  item_t* items_find(item_t* items, size_t log2n, unsigned id) { // YOU ARE NOT SUPPOSED TO MODIFY THIS.
       for (size_t i = 0; i < (1 << log2n); ++i) {
    if (items[i].id == id)</pre>
                 return &items[i];
       return NULL;
  }
24
  void item_init(item_t* item, uint32_t id, const char* data) {
       // YOU CAN MODIFY THIS.
       item->id = id;
       if (data != NULL)
30
           memcpy(item -> data, data, ITEM_DATALEN);
32
            memset(item->data, 0, ITEM\_DATALEN);
  }
```


Questions:

- 9. What is the source of data cache misses in function items_find? Explain.
- 10. Propose a strategy to decrease the number data cache misses caused by function <code>items_find</code>. Test your approach on the Gecko board. What is the new number of cache misses? You can modify only function <code>items_init</code>. You can also modify struct <code>items_t</code> as long as it holds the ID-data relationship.



Notice that function items_find accesses items_t objects that are adjacent in memory.

page 6 of 8 Last change: 01/11/2024 Version: 1.0



Task 3: Optimize Matrix-Vector Multiplication

Consider ./cache/tasks/src/task3.c. In this file, function multiply is defined as:

```
/**
 * @brief Multiplies the matrix with the input vector.
 * Writes to the output vector.
 */
static void multiply() {
    // YOU CAN MODIFY THIS.

for (int j = 0; j < MATRIX_N; ++j) {
    for (int i = 0; i < MATRIX_N; ++i) {
        out_vector[i] += matrix[i][j] * in_vector[j];
    }
}</pre>
```

Questions:

- 11. Explain the terms row-major and column-major order. Which approach is used in C?
- 12. What accesses cause cache misses in function multiply?
- 13. Propose a strategy to decrease the number data cache misses caused by function multiply.

Version: 1.0 Last change: 01/11/2024 page 7 of 8



Task 4: Bouncing Ball Example

Consider ./cache/tasks/src/task4.c. In this file, functions bouncing_ball and init_dcache are defined as:

```
// old base address
  #define LEDS_OLD_BASE 0x50000800ull
  // new base address
  #define LEDS_NEW_BASE 0x08000800ull
  // pixel-based control of LEDs
  #define LEDS_LEDS_OFFSET 0x400ull
  // the base address is configurable.
  // defines the offset of the base address register.
 #define LEDS_BASEADDR_OFFSET 0x7FCull
  void init_dcache() {
      // YOU CAN MODIFY THIS.
      dcache_enable(0);
      dcache_write_cfg(CACHE_FOUR_WAY | CACHE_SIZE_4K | CACHE_REPLACE_LRU |
      CACHE_WRITE_BACK);
18
      dcache_enable(1);
  }
20
  void bouncing_ball() {
    // YOU CAN MODIFY THIS.
      int xdir, ydir, xpos, ypos, index;
24
      volatile unsigned int* leds = (unsigned int*)(LEDS_NEW_BASE + LEDS_LEDS_OFFSET)
      xdir = ydir = 1;
26
      xpos = ypos = 5;
      while (1) {
          index = ypos * 12 + xpos;
          leds[index] = 0;
          if (ypos = 8)
               ydir = -1;
           if (ypos = 0)
               ydir = 1;
           if (xpos == 11)
               \times dir = -1;
           if (xpos == 0)
               xdir = 1;
          ypos += ydir;
          xpos += xdir;
          index = ypos * 12 + xpos;
          leds[index] = swap_u32(2);
          for (volatile long i = 0; i < 100000; i++)
```

Questions:

- 14. Why does not the bouncing ball work as expected? You should be observing no change in the LEDs. The expected behavior is a single pixel moving and reflects as it bounces at the edges.
- 15. Propose two approaches to fix the behavior.

page 8 of 8 Last change: 01/11/2024 Version: 1.0