# Distributed Memory Machines and Programming

https://sites.google.com/lbl.gov/cs267-spr2023/

Slides from the CS267 collection




#### **Outline**

- Distributed Memory Architectures
  - Properties of communication networks
  - Topologies
  - Performance models
- ° Programming Distributed Memory Machines using Message Passing
  - Overview of MPI
  - Basic send/receive use
  - Non-blocking communication
  - Collectives

# **Historical Perspective**


- Early distributed memory machines were:
  - Collection of microprocessors.
  - Communication was performed using bi-directional queues between nearest neighbors.
- Messages were forwarded by processors on path.
  - "Store and forward" networking
- There was a strong emphasis on topology in algorithms, in order to minimize the number of hops = minimize time



# **Performance Properties of a Network: Latency**

- Diameter: the maximum (over all pairs of nodes) of the shortest path between a given pair of nodes.
- Latency: delay between send and receive times
  - Latency tends to vary widely across architectures
  - Vendors often report hardware latencies (wire time)
  - Application programmers care about software latencies (user program to user program)
- ° Observations:
  - Latencies differ by 1-2 orders across network designs
- ° Latency is key for programs with many small messages

# End to End Latency (1/2 roundtrip) Over Time



Latency has not improved significantly, unlike Moore's Law

# Performance Properties of a Network: Bandwidth

- ° The bandwidth of a link = # wires / time-per-bit
- Bandwidth typically in Gigabytes/sec (GB/s),
   i.e., 8\* 2<sup>20</sup> bits per second
- Effective bandwidth is usually lower than physical link bandwidth due to packet overhead.

Bandwidth is important for applications with mostly large messages


Routing and control header

Data payload

Error code


Trailer

# **Bandwidth Chart**



# Performance Properties of a Network: Bisection Bandwidth

- Bisection bandwidth: bandwidth across smallest cut that divides network into two equal halves
- ° Bandwidth across "narrowest" part of the network



 Bisection bandwidth is important for algorithms in which all processors need to communicate with all others

# **Linear and Ring Topologies**

° Linear array



- Diameter = n-1; average distance ~n/3.
- Bisection bandwidth = 1 (in units of link bandwidth).
- ° Torus or Ring




- Diameter = n/2; average distance ~ n/4.
- Bisection bandwidth = 2.
- Natural for algorithms that work with 1D arrays.

# Meshes and Tori – used in Hopper


#### Two dimensional mesh

- Diameter = 2 \* (sqrt( n ) 1)
- Bisection bandwidth = sqrt(n)



#### Two dimensional torus

- Diameter = sqrt( n )
- Bisection bandwidth = 2\* sqrt(n)




- Generalizes to higher dimensions
  - Cray XT (eg Hopper@NERSC) uses 3D Torus
- Natural for algorithms that work with 2D and/or 3D arrays (matmul)


10

# **Hypercubes**

- $^{\circ}$  Number of nodes n = 2<sup>d</sup> for dimension d.
  - Diameter = d.



- ° Popular in early machines (Intel iPSC, NCUBE).
  - Lots of clever algorithms.
  - See 1996 online CS267 notes.
- ° Greycode addressing:
  - Each node connected to d others with 1 bit different.





#### **Trees**

- ° Diameter = log n.
- ° Bisection bandwidth = 1.
- ° Easy layout as planar graph.




- ° Fat trees avoid bisection bandwidth problem:
  - More (or wider) links near top.
  - Example: Thinking Machines CM-5.






#### **Butterflies**

- Really an unfolded version of hypercube.
- A d-dimensional butterfly has (d+1) 2<sup>d</sup> "switching nodes" (not to be confused with processors, which is n = 2<sup>d</sup>)
- Butterfly was invented because hypercube required increasing radix of switches as the network got larger; prohibitive at the time
- Diameter = log n. Bisection bandwidth = n
- No path diversity: bad with adversarial traffic





butterfly switch

Ex: to get from proc 101 to 110, Compare bit-by-bit and Switch if they disagree, else not

# **Dragonflies – used in Edison and Cori**

- Motivation: Exploit gap in cost and performance between optical interconnects (which go between cabinets in a machine room) and electrical networks (inside cabinet)
  - Optical (fiber) more expensive but higher bandwidth when long
  - Electrical (copper) networks cheaper, faster when short

#### ° Combine in hierarchy:

- Several groups are connected together using all to all links, i.e. each group has at least one link directly to each other group.
- The topology inside each group can be any topology.


#### Uses a randomized routing algorithm

- ° Outcome: programmer can (usually) ignore topology, get good performance
  - Important in virtualized, dynamic environment
  - Drawback: variable performance

"Technology-Drive, Highly-Scalable Dragonfly Topology," ISCA 2008


# **Dragonfly in practice**

#### Aries interconnect for an 8 cabinet Cray XC40



Source: European Centre for Medium-Range Weather Forecasts

Source of image on the right (and more info): <a href="https://docs.nersc.gov/systems/cori/interconnect/">https://docs.nersc.gov/systems/cori/interconnect/</a>



# **Performance Models**

# **Latency and Bandwidth Model**

° Time to send message of length n is roughly

- ° Topology is assumed irrelevant.
- ° Often called " $\alpha$ - $\beta$  model" and written Time =  $\alpha$  + n\* $\beta$
- $^{\circ}$  Usually  $\alpha >> \beta >>$  time per flop.
  - One long message is cheaper than many short ones.
  - Can do hundreds or thousands of flops for cost of one message.

$$\alpha + n*\beta << n*(\alpha + 1*\beta)$$

- Lesson: Need large computation-to-communication ratio to be efficient.
- ° LogP more detailed model (Latency/overhead/gap/Proc.)

# Programming Distributed Memory Machines with Message Passing

Slides by
Aydin Buluc, Jonathan Carter, Jim Demmel,
Bill Gropp, Kathy Yelick

# **Message Passing Libraries**

- All communication, synchronization require subroutine calls
  - No shared variables
  - Program run on a single processor just like any uniprocessor program, except for calls to message passing library
- Subroutines for
  - Communication
    - Pairwise or point-to-point: Send and Receive
    - Collectives all processor get together to
      - Move data: Broadcast, Scatter/gather
      - Compute and move: sum, product, max, prefix sum, ... of data on many processors
  - Synchronization
    - Barrier
    - Initial version: no locks because there are no shared variables to protect
  - Enquiries

2/7/23 How many processes? Which one am I? Any messages waiting?

#### **Novel Features of MPI**

- Communicators encapsulate communication spaces for library safety
- Datatypes reduce copying costs and permit heterogeneity
- Multiple communication <u>modes</u> allow precise buffer management
- Extensive <u>collective operations</u> for scalable global communication
- Process topologies permit efficient process placement, user views of process layout
- Profiling interface encourages portable tools

#### **MPI References**

# ° The Standard itself:

- at <a href="http://www.mpi-forum.org">http://www.mpi-forum.org</a>
- All MPI official releases, in both postscript and HTML
- Latest version MPI 4.0, released June 2021

## Other information on Web:

- at <u>http://www.mcs.anl.gov/research/projects/mpi/index.ht</u> m
- pointers to lots of stuff, including other talks and tutorials, a FAQ, other MPI pages

# **Finding Out About the Environment**

- ° Two important questions that arise early in a parallel program are:
  - How many processes are participating in this computation?
  - Which one am I?
- ° MPI provides functions to answer these questions:
  - •MPI\_Comm\_size reports the number of processes.
  - MPI\_Comm\_rank reports the rank, a number between 0 and size-1, identifying the calling process

# Hello (C)


```
#include "mpi.h"
#include <stdio.h>
int main( int argc, char *argv[] )
    int rank, size;
   MPI Init( &argc, &argv );
   MPI Comm rank ( MPI COMM WORLD, &rank );
   MPI Comm size ( MPI COMM WORLD, &size );
   printf( "I am %d of %d\n", rank, size );
   MPI Finalize();
    return 0;
```

#### **Notes on Hello World**

- ° All MPI programs begin with MPI\_Init and end with MPI\_Finalize
- ° MPI\_COMM\_WORLD is defined by mpi.h (in C) or mpif.h (in Fortran) and designates all processes in the MPI "job"
- ° Each statement executes independently in each process
  - including the printf/print statements
- The MPI-1 Standard does not specify how to run an MPI program, but many implementations provide mpirun -np 4 a.out

#### **MPI** Basic Send/Receive

# We need to fill in the details in



# Things that need specifying:

- How will "data" be described?
- How will processes be identified?
- How will the receiver recognize/screen messages?
- What will it mean for these operations to complete?

# **Some Basic Concepts**

- Processes can be collected into groups
- Each message is sent in a <u>context</u>, and must be received in the same context
  - Provides necessary support for libraries
- A group and context together form a communicator
- A process is identified by its <u>rank</u> in the group associated with a communicator
- There is a default communicator whose group contains all initial processes, called MPI\_COMM\_WORLD

# **MPI Datatypes**


- The data in a message to send or receive is described by a triple (address, count, datatype), where
- An MPI datatype is recursively defined as:
  - predefined, corresponding to a data type from the language (e.g., MPI\_INT, MPI\_DOUBLE)
  - a contiguous array of MPI datatypes
  - a strided block of datatypes
  - an indexed array of blocks of datatypes
  - an arbitrary structure of datatypes
- There are MPI functions to construct custom datatypes, in particular ones for subarrays
- May hurt performance if datatypes are complex

27

# **MPI Tags**

- Messages are sent with an accompanying userdefined integer tag, to assist the receiving process in identifying the message
- Messages can be screened at the receiving end by specifying a specific tag, or not screened by specifying MPI\_ANY\_TAG as the tag in a receive
- Some non-MPI message-passing systems have called tags "message types". MPI calls them tags to avoid confusion with datatypes


# MPI Basic (Blocking) Send



MPI\_SEND(start, count, datatype, dest, tag, comm)

- The message buffer is described by (start, count, datatype).
- The target process is specified by dest, which is the rank of the target process in the communicator specified by comm.
- When this function returns, the data has been delivered to the system and the buffer can be reused. The message may not have been received by the target process.

# MPI Basic (Blocking) Receive



MPI\_Send( A, 10, MPI\_DOUBLE, 1, ...)

MPI\_Recv( B, 20, MPI\_DOUBLE, 0, ...)

MPI\_RECV(start, count, datatype, source, tag, comm, status)

- Waits until a matching (both source and tag) message is received from the system, and the buffer can be used
- source is rank in communicator specified by comm, or MPI ANY SOURCE
- tag is a tag to be matched or MPI\_ANY\_TAG
- receiving fewer than count occurrences of datatype is OK, but receiving more is an error
- status contains further information (e.g. size of message) 30

# **A Simple MPI Program**

```
#include "mpi.h"
#include <stdio.h>
int main( int argc, char *argv[])
  int rank, buf;
 MPI Status status;
 MPI Init(&argv, &argc);
  MPI Comm rank ( MPI COMM WORLD, &rank );
  /* Process 0 sends and Process 1 receives */
  if (rank == 0) {
   buf = 123456;
   MPI Send( &buf, 1, MPI INT, 1, 0, MPI COMM WORLD);
  else if (rank == 1) {
   MPI Recv( &buf, 1, MPI INT, 0, 0, MPI COMM WORLD,
              &status );
   printf( "Received %d\n", buf );
  MPI Finalize();
  return 0;
```

# **Retrieving Further Information**

- ° Status is a data structure allocated in the user's program.
- ° In C:

```
int recvd_tag, recvd_from, recvd_count;
MPI_Status status;
MPI_Recv(..., MPI_ANY_SOURCE, MPI_ANY_TAG, ..., &status)
recvd_tag = status.MPI_TAG;
recvd_from = status.MPI_SOURCE;
MPI_Get_count( &status, datatype, &recvd_count);
```


# MPI can be simple

- ° Claim: most MPI applications can be written with only 6 functions (although which 6 may differ)
- Using point-to-point:
  - MPI INIT
  - MPI\_FINALIZE
  - MPI COMM SIZE
  - MPI COMM RANK
  - MPI\_SEND
  - MPI\_RECEIVE

- Using collectives:
  - MPI INIT
  - MPI FINALIZE
  - MPI COMM SIZE
  - MPI COMM RANK
  - MPI BCAST
  - MPI REDUCE

You may use more for convenience or performance

# PI redux: Numerical integration



Mathematically, we know that:

$$\int_{0}^{1} \frac{4.0}{(1+x^2)} dx = \pi$$


We can approximate the integral as a sum of rectangles:

$$\sum_{i=0}^{N} F(x_i) \Delta x \approx \pi$$

Where each rectangle has width  $\Delta x$  and height  $F(x_i)$  at the middle of interval i.

# **Example: Calculating Pi**

E.g., in a 4-process run, each process gets every 4<sup>th</sup> interval. Process 0 slices are in red.



- Simple program written in a data parallel style in MPI
  - E.g., for a reduction (recall "data parallelism" lecture), each process will first reduce (sum) its own values, then call a collective to combine them
- Estimates pi by approximating the area of the quadrant of a unit circle
- Each process gets 1/p of the intervals (mapped round robin, i.e., a cyclic mapping)

### Example: PI in C - 1/2

```
#include "mpi.h"
#include <math.h>
#include <stdio.h>
int main(int argc, char *argv[])
  int done = 0, n, myid, numprocs, i, rc;
  double PI25DT = 3.141592653589793238462643;
  double mypi, pi, h, sum, x, a;
  MPI Init(&argc, &argv);
  MPI Comm size(MPI COMM WORLD, &numprocs);
  MPI Comm rank (MPI COMM WORLD, &myid);
  while (!done) {
    if (myid == 0) {
      printf("Enter the number of intervals: (0 quits) ");
      scanf("%d",&n);
    MPI Bcast(&n, 1, MPI INT, 0, MPI COMM WORLD);
    if (n == 0) break:
```


# Example: PI in C - 2/2

```
h = 1.0 / (double) n;
  sum = 0.0;
  for (i = myid + 1; i \le n; i += numprocs) {
    x = h * ((double)i - 0.5);
    sum += 4.0 / (1.0 + x*x);
  mvpi = h * sum;
  MPI Reduce (&mypi, &pi, 1, MPI DOUBLE, MPI SUM, 0,
             MPI COMM WORLD);
  if (myid == 0)
    printf("pi is approximately %.16f, Error is .16f\n",
            pi, fabs(pi - PI25DT));
MPI Finalize();
return 0;
```

#### **Buffers**

2/7/23


° When you send data, where does it go? One possibility is:



Slide source: Bill Gropp, ANL 38

# **Avoiding Buffering**

- Avoiding copies uses less memory
- ° May use more or less time



This requires that MPI\_Send wait on delivery, or that MPI\_Send return before transfer is complete, and we wait later.

Slide source: Bill Gropp, ANL

# **Blocking and Non-blocking Communication**

- So far we have been using blocking communication:
  - MPI\_Recv does not complete until the buffer is full (available for use).
  - MPI\_Send does not complete until the buffer is empty (available for use).
- Completion depends on size of message and amount of system buffering.

#### **Sources of Deadlocks**

- Send a large message from process 0 to process 1
  - If there is insufficient storage at the destination, the send must wait for the user to provide the memory space (through a receive)
- ° What happens with this code?

Process 0	Process 1
Send(1)	Send(0)
Recv(1)	Recv(0)

 This is called "unsafe" because it depends on the availability of system buffers in which to store the data sent until it can be received

# Some Solutions to the "unsafe" Problem

° Order the operations more carefully:

Process 0	Process 1	
Send(1)	Recv(0)	
Recv(1)	Send(0)	

Supply receive buffer at same time as send:

```
Process 0 Process 1

Sendrecv(1) Sendrecv(0)
```

# More Solutions to the "unsafe" Problem

# Supply own space as buffer for send

Process 0	Process 1
Bsend(1)	Bsend(0)
Recv(1)	Recv(0)

Use non-blocking operations:

Process 0	Process 1	
Isend(1)	Isend(0)	
Irecv(1)	Irecv(0)	
Waitall	Waitall	

# MPI's Non-blocking Operations

Non-blocking operations return (immediately) "request handles" that can be tested and waited on:

° One can also test without waiting:

```
MPI_Test(&request, &flag, &status);
```

Accessing the data buffer without waiting is undefined

# **Multiple Completions**

° It is sometimes desirable to wait on multiple requests:

```
MPI_Waitall(count, array_of_requests,
    array_of_statuses)

MPI_Waitany(count, array_of_requests,
    &index, &status)

MPI_Waitsome(count, array_of_requests,
    array_of_indices, array_of_statuses)
```

There are corresponding versions of test for each of these.

#### **Communication Modes**

- ° MPI provides multiple modes for sending messages:
  - Synchronous mode (MPI\_Ssend): the send does not complete until a matching receive has begun. (Unsafe programs deadlock.)
  - Buffered mode (MPI Bsend): the user supplies a buffer to the system for its use. (User allocates enough memory to make an unsafe program safe.
  - Ready mode (MPI\_Rsend): user guarantees that a matching receive has been posted.
    - Allows access to fast protocols
    - undefined behavior if matching receive not posted
- Non-blocking versions (MPI\_Issend, etc.)
- ° MPI\_Recv receives messages sent in any mode.
- See <a href="https://www.mpi-forum.org">www.mpi-forum.org</a> for summary of all flavors of send/receive