## <u>ois.marechal@epfl.ch</u> ©Industrial Energy Systems Laboratory- LENI-IGM-STI-EPFL 21

### Optimisation models for district energy system design

### Prof. François Marechal

Industrial Process and Energy Systems Engineering
Institute of Mechanical Engineering
School of Engineering
Ecole Polytechnique Fédérale de Lausanne
<a href="http://ipese.epfl.ch">http://ipese.epfl.ch</a>





#### **Content**


- Energy system models
- Energy system integration
  - -Defining the requirement & Resources
  - -Energy conversion
  - -Networks integration
- Multi objective environomic optimisation
  - -Problem statement
  - Optimisation strategy
  - Optimisation tricks
- Conclusions



**EXIPESE** 




### A multi dimension approach



**SIPESE** 

# francois.marechal@epfl.ch ⁰Industrial Energy Systems Laboratory- LENI-IGM-STI-EPFL 2012

#### **Problem statement**



IPESE
INDESTRUM PROCESS AND
INDESTRUM SYSTEMA GOGGNESSION

#### Multi scale approach




Figure 1.15: Log-log plot of the magnitude of the spatial scale to deal with in urban studies.



#### **Energy system design: Industrial Ecology Concepts**

- For a given city: select the optimal energy system
  - -Integration of processes in the urban system

40'000 inhabitants city in Switzerland (1000m alt.)



Energy services to be supplied:

▶ Heat using existing district heating network (seasonal variation in T and load): 3357 kWh<sub>th</sub>/yr/cap

▶ Electricity (seasonal variation): 8689 kWhe/yr/cap

→ Mobility: I 1392 pkm/yr/cap

Waste to be treated (existing facilities for MSW and WWTP):

MSW: 1375 kg/yr/cap

Wastewater: 300 m3/yr/cap

Biowaste: 87.5 kg/yr/cap

Available endogenous resources:

▶ Woody biomass: 18'900 MWh<sub>th</sub>/yr

▶ Geothermal: 9496 MWh<sub>th</sub>/yr

→ Sun (seasonal variation in T and load): 10'328 MWh<sub>th</sub>/yr

 Hydro (existing dams): 187'850 MWh<sub>e</sub>/yr Which resources with which technologies for which services?


▶ Min. Costs and CO2 emissions





### Su

#### Superstructure generation and supply chain synthesis



Heat balance

▶ Heat cascade

**SIPESE** 

Mass balance


▶ Mass balance for each source/sink

Environmental impact

► Choose the supply chain

(1741

#### Input-output models for Swiss Energy System in energyscope.ch





#### Linear programming multi period model

$$\begin{aligned} & \min \mathbf{C}_{\text{tot}} = \sum_{j \in TECH} (\tau j) \mathbf{C}_{\text{inv}}(j) + \mathbf{C}_{\text{maint}}(j)) + \sum_{i \in RES} \mathbf{C}_{\text{op}}(i) \\ & \text{s.t. } \tau(j) = \frac{i_{\text{trate}}(i_{\text{rate}} + 1)^{n(j)}}{(i_{\text{trate}} + 1)^{n(j)} - 1} & \forall j \in TECH \ (1.2) \\ & \mathbf{C}_{\text{inv}}(j) = c_{\text{inv}}(j) \mathbf{F}(j) & \forall j \in TECH \ (1.3) \\ & \mathbf{C}_{\text{maint}}(j) = c_{\text{maint}}(j) \mathbf{F}(j) & \forall j \in TECH \ (1.4) \\ & \mathbf{GWP}_{\text{constr}}(j) = gwp_{constr}(j) \mathbf{F}(j) & \forall j \in TECH \ (1.4) \\ & \mathbf{N}(j) f_{ref}(j) \leq \mathbf{F}(j) & \forall j \in TECH \ (1.6) \\ & \mathbf{N}(j) f_{ref}(j) \leq \mathbf{F}(j) & \forall j \in TECH \ (1.7) \\ & \mathbf{F}_{\mathbf{f}}(j,t) \leq \mathbf{F}(j) c_{p_{\mathbf{f}}}(j,t) & \forall j \in TECH \ (1.7) \\ & \mathbf{F}_{\mathbf{f}}(j,t) \leq \mathbf{F}(j) c_{p_{\mathbf{f}}}(j,t) & \forall j \in TECH \ (1.7) \\ & \mathbf{F}_{\mathbf{f}}(j,t) \leq \mathbf{F}(j) c_{p_{\mathbf{f}}}(j,t) & \forall j \in TECH \ (1.9) \\ & \mathbf{C}_{\mathbf{op}}(i) = \sum_{i \in T} c_{op_{\mathbf{f}}}(i,t) \mathbf{F}_{\mathbf{f}}(i,t) t_{op_{\mathbf{f}}}(t) & \forall i \in RES \ (1.10) \\ & \mathbf{GWP}_{\mathbf{op}}(i) = \sum_{i \in T} c_{op_{\mathbf{f}}}(i,t) \mathbf{F}_{\mathbf{f}}(i,t) t_{op_{\mathbf{f}}}(t) & \forall i \in RES \ (1.11) \\ & \sum_{i \in T} \mathbf{F}_{\mathbf{f}}(i,t) t_{op_{\mathbf{f}}}(j) \leq avail(i) & \forall i \in RES \ (1.12) \\ & \sum_{i \in TECH} \mathbf{F}_{\mathbf{f}}(i,t) \mathbf{F}_{\mathbf{f}}(i,t) + \sum_{j \in STO} (\mathbf{Sto}_{\mathbf{out}}(j,l,t) - \mathbf{Sto}_{\mathbf{in}}(j,l,t)) - \mathbf{EndUses}(l,t) = 0 & \forall l \in L, \forall t \in T \ (1.13) \\ & \mathbf{F}_{\mathbf{f}}(j,t) = \mathbf{F}_{\mathbf{f}}(j,t) + \mathbf{1} + t_{op_{\mathbf{f}}}(t) & \sum_{l \in L(i_{l};i_{\text{stoto}},i,l,j) > 0} & \forall j \in STO, \forall l \in L, \forall t \in T \ (1.14) \\ & i \in L(i_{l};i_{\text{stoto}},i,l,j) - \mathbf{1} = \mathbf{0} & \forall j \in STO, \forall l \in L, \forall t \in T \ (1.15) \\ & \mathbf{Sto}_{\mathbf{in}}(j,l,t), (|\tau_{l};i_{\text{oto}},i_{\text{ott}}(j,l)| - 1) = 0 & \forall j \in STO, \forall l \in L, \forall t \in T \ (1.16) \\ & \mathbf{F}_{\mathbf{f}}(j,t) = \mathbf{F}_{\mathbf{f}}(j,t) \mathbf{F}_{\mathbf{$$



#### **MILP** model

$$\sum_{j' \in \mathit{TECH}} f_{min,\%}(j) \sum_{t \in \mathit{T}} \mathbf{F_t}(j',t) t_{op}(t) \leq \sum_{t \in \mathit{T}} \mathbf{F_t}(j,t) t_{op}(t) \leq \sum_{j' \in \mathit{TECH}} f_{max,\%}(j) \sum_{t \in \mathit{T}} \mathbf{F_t}(j',t) t_{op}(t)$$

 $\forall eut \in EUT, \forall j \in TECH \ OF \ EUT(eut) \ (1.22)$ 

$$\mathbf{F_t}(j,t)\sum_{t\in T}t_{op}(t) \ge \sum_{t\in T}\mathbf{F_t}(j,t)t_{op}(t)$$

 $\forall j \in TECH \ OF \ EUC(MobPass) \cup TECH \ OF \ EUC(MobFreight), \forall t \in T \ (1.23)$ 

$$\mathbf{F}(StoHydro) \le f_{max}(StoHydro) \frac{\mathbf{F}(NewHydroDam) - f_{min}(NewHydroDam)}{f_{max}(NewHydroDam) - f_{min}(NewHydroDam)}$$
(1.24)

$$Sto_{in}(StoHydro, Elec, t) \le F_t(HydroDam, t) + F_t(NewHydroDam, t)$$
  $\forall t \in T$  (1.25)

$$\mathbf{F}(DHN) \ge \sum_{j} \mathbf{F}(j) \tag{1.26}$$

 $j \in TECH \ OF \ EUT(HeatLowTDHN)$ 

$$\sum_{j \in TECH \ OF \ EUT(HeatLowTDHN)} \mathbf{F}(j) \ge \%_{Peak_{DHN}} \max_{t \in T} \left\{ \mathbf{EndUses}(HeatLowTDHN, t) \right\}$$

$$(1.27)$$

$$\mathbf{F}(Grid) \ge \frac{9400}{c_{inv}(Grid)} \frac{\mathbf{F}(Wind) + \mathbf{F}(PV)}{f_{max}(Wind) + f_{max}(PV)} \tag{1.28}$$

$$\mathbf{F}(PowerToGas) = \max\{\mathbf{F}(PowerToGas), \mathbf{F}(GasToPower)\}$$
(1.29)





#### **MILP** model

Parameter	Units	Description					
endUses <sub>year</sub> (eui, s)	[GWh/y] <sup>a</sup>	Annual end-uses in energy services per sector					
endUsesInput(eui)	$[GWh/y]^a$	Total annual end-uses in energy services					
$\tau$ (tech)	[-]	Investment cost annualization factor					
$i_{rate}$	[-]	Real discount rate					
%public,min,%public,max	[-]	Upper and lower limit to % <sub>Public</sub>					
%rail,min, %rail,max	[-]	Upper and lower limit to %Rail					
$\%_{dhn,min}, \%_{dhn,max}$	[-]	Upper and lower limit to % <sub>Dhn</sub>					
$t_{op}(t)$	[h]	Time periods duration					
$% _{lighting}^{\prime }(t)$	[-]	Yearly share (adding up to 1) of lighting end-uses					
$%_{sh}(t)$	[-]	Yearly share (adding up to 1) of SH end-uses					
$f(res \cup tech \setminus sto, l)$	$[GW]^b$	Input from (< 0) or output to (> 0) layers. $f(i, j) = 1$					
j (res 0 tech (sto, t)		if $j$ is main output layer for technology/resource $i$					
$f_{ref}(tech)$	$[GW]^{bc}$	Reference size with respect to main output					
$c_{inv}(tech)$	[MCHF/GW] <sup>bc</sup>	Technology specific investment cost					
$c_{maint}(tech)$	[MCHF/GW/y] <sup>bc</sup>	Technology specific yearly O&M cost					
$gwp_{constr}(tech)$	[ktCO <sub>2</sub> -eq./GW] <sup>bc</sup>	Technology construction specific GHG emissions					
n(tech)	[y]	Technology lifetime					
$f_{min}, f_{max}(tech)$	$[GW]^{bc}$	Min./max. installed size of the technology					
$f_{min,\%}, f_{max,\%}(tech)$	[-]	Min./max. relative share of a technology in a layer					
avail(res)	[GWh/y]	Resource yearly total availability					
$c_{p,t}(tech,t)$	[-]	Period capacity factor (default 1)					
$c_p(tech)$	[-]	Yearly capacity factor					
$c_{op}(res,t)$	[MCHF/GWh]	Specific cost of resources					
$gwp_{ov}(res)$	[ktCO <sub>2</sub> -eq./GWh]	Specific GHG emissions of resources					
- r		Efficiency [0; 1] of storage input from/output					
$\eta_{sto,in}, \eta_{sto,out}(sto, l)$	[-]	to layer. Set to 0 if storage not related to layer.					
$%_{loss}(eut)$	[-]	Losses [0;1] in the networks (grid and DHN)					
$\%_{Peak_{DHN}}$	[-]	Ratio peak/max. average DHN heat demand					






# francois.marechal@epfl.ch @Industrial Energy Systems Laboratory- LENI-IGM-STI-EPFL 2012

#### Seasonal operation (independent multi-period)

Example of summer and winter system operation








#### Optimal pathways and technology selection

Example of wood in environomic configurations







# francois.marechal@epfl.ch @Industrial Energy Systems Laboratory- LENI-IGM-STI-EPFL 2012


#### **Competitions and synergies**

Example of interaction between MSWI and WWTP in summer



- Usage of waste heat from WWTP
  - reduces supplementary requirement
- More electricity available from MSWI
  - reduces import





Deep aquifer competing with EGS for CHP & Wood to SNG conversion



# francois.marechal@epfl.ch ondustrial Energy Systems Laboratory- LENI-IGM-5TI-EPFL 2012








### <u>sis.marechal@epfl.ch</u> °Industrial Energy Systems Laboratory- LENI-IGM-STI


### Defining the requirement of a building

- Definition of the energy requirement
  - Heating
  - Air renewal
  - Hot water
  - Waste Water
  - Air renewal






### **Local heat recovery**



SIPESE DEDICTION AND

### Heat recovery and reuse in a building




COP = 5 to 6





### **Building renovation**



Heat required : - 60%


Nb of days : - 16%

Peak power: - 37 %

Heating temperature:

COP: + 10%


Investment period : constant!







#### Changing the scale

• Characterizing the services






Seasonal temperature variation




**CIPESE** 



### System integration



#### Integrating the demand: the whole canton









#### The urban system integration

- Multi Energy services
  - Electricity
  - Heating
  - Cooling
  - Hot water
  - Refrigeration
  - Industrial processes
- Heat integration
  - Composite curves
  - Heat-temperature diagrams
    - thermal distribution
- → Seasonal profiles
  - stochastic!
- **→**Evolution scenarios
  - **→**buildings stock
  - **→**refurbishment

#### Composite curve of the Geneva canton







#### Heat pumps and local renewable resources

#### Local resources

- Air
- Geothermal
- Surface water (lake -river)
- Waste water
- Industry waste heat












### <u>Icois.marechal@epfl.ch</u> °Industrial Energy Systems Laboratory- LENI-IGM-5TI-EPFL 201 francois.marechal@epfl.ch °Laboratory for Industrial Energy Systems - LENI ISE-STI-EPFL - Marsh 2

### Resources localisation






# .marechal@epfl.ch @Industrial Energy Systems Laboratory- LENI-IGM-STI-EPFL 2012

#### Integrate resources

Table 4

Theorical COP efficiency factors.

Туре	Size	$T_{ m lm}^{ m cold}$	$\eta_{\text{COP}}(2005)$	$\eta_{\text{COP}}(2030)$	
Air/water	Local	$T_{ext}$ – 5	0.34	0.38	
Ground/water	Local	2	0.43	0.48	
Water/water	Local	3	0.43	0.48	
Geostructure/water	Local	6	0.43	0.48	
Surface water/water	Centralized	6	0.55	0.60	
WTP/water	Centralized	12	0.55	0.60	







Fig. 13. COP map considering the available resources for heat pumping in 2030.




#### Waste water reuse District Heating Perspective







#### Industrial Symbiosis: Valorising waste heat




Raw






#### Waste management






#### District heating: infrastructure development




Journée type Janvier - Consommation chaleur normalisée Normalised daily requirement (kW/m2)



### <u>ncois.marechal@epfl.ch</u>ndustrial Energy Systems Laboratory- LENI-IGM-STI-EP

### Interest of district heating systems

- Size (mutualisation)
  - efficiency
  - $-\cos t$
- Higher technicity
- Energy services companies
- Access to local Resources
  - Water
  - Biomass
  - -Geothermal
- Optimal Management
  - Peak shaving
  - -Market



**Building** 

District heating





#### Heat distribution cost: cts CHF/annual kWh

- ▶ Building density
  - ▶ nb + m2
- Power density
- Annual energy

$$L_{DHN} = 2(N_b - 1)K\sqrt{\frac{A_h}{N_b}}$$

$$T_{supply}^* = T_{return} + (T_{supply} - T_{return}) \cdot (1 + f_{loss,ref} \frac{T_{supply} - T_{ground}}{T_{ref} - T_{ground}})$$

$$f_{loss,ref} = \frac{T_{supply} - T_{ground}}{T_{ref} - T_{ground}}$$

$$\dot{Q}_{DHN} = \dot{m}_{DHN} cp_{fluid} (T^*_{supply} - T_{return})$$

$$d_{DHN} = \sqrt{\frac{4\dot{m}_{DHN}}{\pi v_s \rho(T_{supply}^*)}}$$

$$C_{DHN} = rac{(c_1 d_{DHN} + c_2) L_{DHN} rac{1}{ au}}{\dot{Q}_{DHN}} \left[ ext{CHF/kWh} 
ight]$$




Table 4.1: Typical cost of network pipes, for diameters between 25mm and 300mm.


Parameters	values											
pipe diameter [mm]	25	32	40	50	65	80	100	125	150	200	250	300
pipe cost [CHF/m]	950	950	1000	1200	1250	1350	1470	1600	1750	2000	2500	3000







#### **District heating**



What is the temperature of the network

# <u>cois.marechal@epfl.ch</u> ⁰Industrial Energy Systems Laboratory- LENI-IGM-STI-EPFL 2

#### **Energy system design**

**Resources**: solar, geothermal, wind, water **Efficiency**: refurbishment, heat recovery


**Energy conversion**: heat pumps, cogeneration, boilers

**Energy management**: storage tanks, batteries

**Investments**: size, location

**Interconnections**: multi-energy grids

**Operation**: peak shaving, flexibility, security of supply





### Superstructure slave optimization model

$$\min \sum_{\mathbf{s}} \mathbf{OPEX}(\mathbf{y_s}, \mathbf{y_{s,p}}, \mathbf{u_s}, \mathbf{u_{s,p}}) + \sum_{\mathbf{p}=1}^{\mathbf{N_P}} (\mathbf{\dot{I}_p} \times \mathbf{t_{CO_2}} \times \triangle \mathbf{p})$$
Op. utilization levels

Power Facts

Power

Local balancing equations

Local balancing layers  $(L_{bl})$ 

Power / material streams  $\dot{\mathbf{E}}^{+/-} \dot{\mathbf{M}}^{+/-}$ 

Global balancing layers  $(L_{ba})$ 

Power / material streams


$$\dot{\mathbf{E}}_{\mathbf{g},\mathbf{L_{bg}},\mathbf{s_e},\mathbf{p}}^{+/-}$$
  $\dot{\mathbf{M}}_{\mathbf{g},\mathbf{L_{bg}},\mathbf{s_f},\mathbf{p}}^{+/-}$ 

Heat cascading layer  $(L_h)$ 

 $\frac{\text{Hot \& cols streams}}{\mathbf{\dot{Q}_{g,L_h,s_{j/i},p}^{+/-}}}$ 

Distribution network

- Transportation
- ✓ Material flows
- ✓ Trade-off between transportation systems
  - √ Heat cascade restriction
  - √ Layout (GIS)
  - ✓ Operating schedule
  - ✓ Fluid type
  - ✓ Heat flows



**Network equations** 

# francois.marechal@epfl.ch ©Industrial Energy Systems Laboratory- LENI-IGM-STI-EPFL 2012


#### List of technology options in the data base

#### **Conversion Technologies** Resources **Networks** Solar Waste-water Local district Gas engine *Irradiation* treatment heating networks Geothermal Gas boiler Gas turbine Global district (centralized) heat heating networks Gas boiler Natural gas Combined cycle (decentralized) *Electricity* **Services** *Incinerator* Steam cycle import Woody Energy services biomass Heat pump Biomass boiler Domestic Space heating hot water Waste to be treated **Biomethanation** Biogas boiler Municipal Waste-**Electricity** solid waste water Biogas turbine Gasifier Municipal Organic waste Air dryer Biogas engine





#### Each node is a process with network connections



#### Multi-period problem (for the day of a month)

node k

Heat exchange by heat cascade model

Electricity balance

Technologies w, @node k period p Demand @node k, period p  $\sum u_{w,k,p} \mathbf{q}_{w,k,p,r} + \sum \mathbf{Q}_{k,p,d,r} + R_{k,p,r+1} - R_{k,p,r} = 0$  $\sum_{w=1}^{n_w} u_{w,k,p} \mathbf{e}_{w,k,p,r} + \sum_{d=1}^{n_d} \mathbf{e}_{k,p,d,r} + E_{k,p}^+ - E_{k,p}^- = 0$   $E_{k,p}^+ \ge 0, \quad E_{k,p}^- \ge 0$  $E_{k,p}^+ \ge 0, \quad E_{k,p}^- \ge 0$ Existence: w in location k  $\forall w = 1,...,n_w \ \forall p = 1,...,n_n \ \forall k = 1,...,n_k$  $y_{w,k,p} \mathbf{u_{min_w}} \le u_{w,k,p} \le y_{w,k,p} \mathbf{u_{max_w}}$  $y_{w,k} \mathbf{u_{min_w}} \le u_{w,k} \le y_{w,k} \mathbf{u_{max_w}} \quad \forall k, w$  $u_{w,k,p} \le u_{w,k} \quad \forall w, k, p$ Water: mi₀, Water: mii, Tin, hin Tin, hin  $y_{i,k} \cdot \dot{m}_{min} \le \dot{m}_{i,k,p} \le y_{i,k} \cdot \dot{m}_{max}$ 

 $\dot{m}_{i,k,p}$ 

$$\dot{Q}_{k,p}^{loss} = \sum_{n_{node}}^{n_{node}} q^{loss}(T_{i,k}^{in}) \cdot \dot{m}_{i,k,p}$$

return: moo. Tout, hout

 $Cost_{pipe} = \sum \qquad \sum \quad (y_{i,k} \cdot cf_{pipe} \cdot length_{i,k} + \dot{m}_{i,k}^{max} \cdot cd_{pipe} \cdot length_{i,k})$  $i=1, i \neq k \ k=1, k \neq i$ 


 $\dot{E}_{pump,i,k,p} = y_{i,k} \cdot e^0_{pipe} \cdot length_{i,k} + \dot{m}_{i,k,p} \cdot e^1_{pipe,i,k}$ 

return: moi, Tin, hin

S. Fazlollahi, G. Becker and F. Maréchal. Multi-Objectives, Mul.-Period Optimization of district energy systems: II-Daily thermal storage, in Computers & Chemical Engineering, 2013a


 $\dot{m}_{i,k,p} \le \dot{m}_{i,k}^{max}$ 








#### District heating supestructure



Routing algorithm



#### Management of storage during the day (multi-period/multi-time)



IPESE
INDIRECTIONAL PROCESS AND
ISOTRECE STATISTICAL PROCESS AND

#### Storage tank model

Storage tank Model

$$\sum_{t=1}^{nt} (cf_{hs} \cdot d_{p,t} \sum_{l=1}^{nl} (\sum_{h_l=1}^{ns_{h,l}} \mathbf{f}_{u,p,t} \dot{M}_{h,l,u,p,t} - \sum_{c_l=1}^{ns_{c,l}} \mathbf{f}_{u,p,t} \dot{M}_{c,l,u,p,t})) = 0$$
(13)

$$M_{l,p,t} = M_{0,l} + \sum_{t=1}^{t} (cf_{hs} \cdot d_{p,t} \sum_{l=1}^{nl} (\sum_{h_{l}=1}^{ns_{h,l}} f_{u,p,t} \dot{M}_{h,l,u,p,t} - \sum_{c_{l}=1}^{ns_{c,l}} f_{u,p,t} \dot{M}_{c,l,u,p,t}))$$

$$\forall l = 1..., nl \quad \forall t = 1..., nt$$
(14)

$$M_{l,p,t} > 0$$
  $M_{0,l} > 0$   $\forall l = 1..., nl$   $\forall t = 1..., nt$  (15)

$$\sum_{l=1}^{nl} M_{l,t} < M_{tot} \qquad \sum_{l=1}^{nl} M_{0,l} < M_{tot} \qquad \forall l = 1..., nl \quad \forall t = 1..., nt$$
 (16)

$$M_{0,l} + \sum_{t=1}^{t} (cf_{hs} \cdot d_{p,t} \sum_{l=1}^{nl} (\sum_{h_{l}=1}^{ns_{h,l}} f_{u,t} \dot{M}_{h,l,u,p,t}))$$

$$- \sum_{t=1}^{t-1} (cf_{hs} \cdot d_{p,t} \sum_{l=1}^{nl} (\sum_{h_{l}=1}^{ns_{c,l}} f_{u,p,t} \dot{M}_{c,l,u,p,t})) - M_{l,p,t} \ge 0 \quad \forall l = 1..., nl \quad \forall t = 1..., nt$$
(17)

$$\dot{Q}_{c,l} = \mathbf{f}_{u,p,t} \cdot \dot{M}_{c,l,u,p,t} \cdot c_p \cdot (T_{st,l+1} - T_{st,l})$$
(18)

$$\dot{Q}_{h,l} = \mathbf{f}_{u,p,t} \cdot \dot{M}_{h,l,u,p,t} \cdot c_p \cdot (T_{st,l} - T_{st,l+1})$$
(19)

Heat losses in storage tanks

$$\dot{Q}_{hl,l,p,t} = k_{hl} \cdot \frac{f_{hl} \cdot 4 \cdot M_{l,p,t}}{\rho \cdot d} \cdot (T_{st,l} - T_a) \qquad \forall l = 1..., nl \quad \forall t = 1..., nt$$
 (20)

with 
$$A = \pi \cdot d \cdot h, V = \pi \cdot \frac{d^2}{4} \cdot h$$

#### Variables

number of cycles of period poperating time of time slice t in period p

electricity purchase costfor time slice t in period p $c_{el,p,t}^{-l,p,t}$   $c_{f,p,t}^{+}$   $E_{f,u,p,t}^{+}$ Electricty selling price for time slice t in period p. is the fuel price for time slice t in period p.

nominal energy delivered to unit u for time slice t in period p

 $\dot{E}_{el,u,p,t}$ nominal electricity demand<sup>(+)</sup> or  $excess^{(-)}$  of unit u for time slice t in period p. is the nominal operating cost per hour of unit u (excluding the fuel and elec-

tricity costs).

multiplication factor of unit u for time slice t in period p $f_{u,p,t}$ 

use of unit u in time slice t in period p.  $y_{u,p,t}$ 

nominal heat load of hot stream h in sub-system s and temperature interval k,  $Q_{h,s,k,u,p,t}$ 

belonging to unit u and in time slice t.

 $\dot{Q}_{hts(s),s,k,p,t}^{-}$ Heat supplied to the heat transfer fluid in the temperature interval k and in

time slice t)


 $\dot{R}_{s,k,p,t}$ cascaded heat to the lower temperature interval k in sub-system s.

 $cf_{hs}$ unit conversion factor

 $\dot{M}_{h,l,u,p,t}$ nominal flow-rates of the hot stream of storage tank

 $\dot{M}_{c,l,u,p,t}$ nominal flowrate of the cold stream respectively in time slice t.

initial water content of tank l.




Units for heat integration

HL: Heat losses



# francois.marechal@epfl.ch oIndustrial Energy Systems Laboratory- LENI-IGM-STI-EPFL 2012

#### Comparison between storage and not in the central plant








### <u>cois.marechal@epfl.ch</u> ©Industrial Energy Systems Laboratory- LENI-IGM-STI


#### Evaluation of the operational cost

- 40 time steps:
  - 7 days\*5 sequence + I Extreme \* 5
- Probability of appearance
  - =>number of days

20 x 8760 hours



175'200 hours








### MILP problem size

How we can reduce the optimization size (variables & constraints) and computational load?

35	312	8760
7400	65000	1830000
6200	54000	1520000
400	3700	104000
23	85	2700
	6200 <b>400</b>	7400 65000 6200 54000 400 3700






No. time step

While achieving accurate representation of data!

**CIPESE** 


#### I-Data structuring: Typical periods selection method



#### I-Data structuring: Typical periods selection method

raw the Pareto frontier of each performance indicator and select  $N_k^\prime$  , the minimum accepted number of clusters

 $N_k'$ : the indicators' improvement on the Pareto frontier from  $N_k'$ to  $N_k'$ + 1 is not significant




At least we need 5 clusters

Normalized Pareto frontiers of performance indicators for each type of attributes

# <u>francois.marechal@epfl.ch</u> <sup>o</sup>Industrial Energy Systems Laboratory- LENI-IGM-STI-EPFL 2012

#### Typical days definition

- 40 time steps: 7 days\*5 sequence + I Extreme \* 5
   => instead of 8760 hours
- Probability of appearance (number of days)
- Using clustering techniques




Validation is performed

- 0.3-4.1% errors
- 40 times faster



# <u>francois.marechal@epfl.ch</u> ⁰Industrial Energy Systems Laboratory- LENI-IGM-STI-EPFL 2012

#### The difficulty of the urban size



How we can reduce the optimization size and computational load considering the number of subsystems?






#### **GIS Clustering**

#### Cluster the city into limited number of "integrated zones"!


 The integrated zone is an area where resources, energy conversion technologies, and buildings are aggregated







### **GIS** clustering



Subsystems 60,000 buildings 13 integrated zones


Constraints (x10<sup>3</sup>) 6,480,000 210

Each building has a probability of being connected to the grid

Reduce the optimization size significantly

**CIPESE** 


### Master slave decomposition



**SIPESE** 

#### Multi-objective optimisation: application to a canton





## ncois.marechal@epfl.ch ©Industrial Energy Systems Laboratory- LENI-IGM-STI-F

#### **Topics covered**

- Tools for the analysis and design of more efficient and sustainable industrial and urban energy systems, with a particular focus on:
  - Energy system models
    - System integration: multi-period
    - Optimal system operation : multi-time (typical days)
  - -Thermo economic and environomic models
    - Energy system design (location, selection and size of equipment)
    - Superstructures: list of options
  - Multi objective optimisation techniques
  - Decision support



