



Focused Lens-End Lamps

Line No.	Part No.	Volts	Amps	Lux*	Color Temp. Degrees Kelvin	Life Hours	Vacuum Or Gas	Filament Type	Base Type	Drawing
1	L1005	2.5	0.350	1,550	2,200	25,000	V	C-6	Brass	A
2	L1005A	2.5	0.350	1,550	2,200	25,000	V	C-6	Brass	C
3	L1026A	2.5	0.350	2,000	2,250	10,000	V	C-2R	Brass	C
4	L1023	2.5	0.350	2,100	2,250	15,000	V	C-6	Brass	A
5	L1006	3.5	0.450	1,600	2,230	30,000	G	C-6	Brass	A
6	L1024	3.5	0.560	3,800	2,490	4,500	G	C-6	Brass	A
7	L1024A	3.5	0.560	3,800	2,490	4,500	G	C-6	Brass	C
8	L1021	3.5	0.600	12,000	2,850	100	Krypton	C-6	Brass	A
9	L1030	3.5	1.200	16,000	2,950	150	Halogen	C-6	Brass	A
10	L1007	5.0	0.160	880	2,300	12,500	V	C-2R	Brass	B
11	L1025	5.0	0.240	1,200	2,450	10,000	V	C-2R	Brass	B

* Lux at 50mm. Light Distribution page 7, figure 1.



10 Technology Drive
Peabody, MA 01960
USA
Tel: 978-818-6180
Fax: 978-818-6181
ilsales@intl-lighttech.com
www.intl-lighttech.com